

Jaydex Adaptor or Rainwater Head

*Jaydex base sheet membrane to be torched into recess. A hole is cut in base sheet for side drain and base sheet torched and side drain pushed into molten bitumen and left to cool. Jaydex cap sheet membrane is torched over side drain, then hole cut in side drain to let water exit.

Jaydex Sheet Membrane

Jaydex Side Drain

Asphalt

Recess in Substrate

Jaydex Primer

Jaydex Sheet Membrane

Substrate

Down Pipe

Asphalt

Jaydex Sheet Membrane

Double Thickness

Jaydex Primer

Jaydex Side Drain

Recess and Jaydex Base sheet membrane gusset to extend 40mm past perimeter of Jaydex side drain flange.

DECK

SIDE DRAIN OUTLET


Single Sheet Torch-On Membrane System

Asphaltic Concrete Overlay Finish

DK/03/SS/AC

Date: 06/06 Drawn: SB

JAYDEX
INTERNATIONAL · LIMITED



UNIT 3c-3 MARKEN PLACE,
GLENFIELD, AUCKLAND

PHONE Bus. (09) 444-1751
FAX (09) 444-0132

E-MAIL jaydex@xtra.co.nz
sales@jaydex.com

Disclaimer

The detailed drawings as outlined are based on our experience and application procedures and represent the latest information available. No responsibility is taken for uses to which this information may be put, but we advise that where the application is in complete conformity with the appropriate specification a warranty maybe available.

We reserve the right to alter or up date the information parameter at anytime without prior notice. *Copyright